


Unsupervised Learning: Word Embedding

Word Embedding

- Machine learns the meaning of words from reading a lot of documents without supervision



1-of-N Encoding

apple = [1 0 0 0 0]


bag = [0 1 0 0 0]

cat = [0 0 1 0 0]


dog = [0 0 0 1 0]

elephant = [0 0 0 0 1]

Word Embedding



Word Class



Word Embedding

- Machine learns the meaning of words from reading a lot of documents without supervision
- A word can be understood by its context

蔡英文、馬英九 are something very similar

You shall know a word by the company it keeps

馬英九 520宣誓就職

蔡英文 520宣誓就職



How to exploit the context?

- **Count based**

- If two words w_i and w_j frequently co-occur, $V(w_i)$ and $V(w_j)$ would be close to each other

- E.g. Glove Vector:

<http://nlp.stanford.edu/projects/glove/>

$V(w_i) \cdot V(w_j)$

Inner product



$N_{i,j}$

Number of times w_i and w_j
in the same document


- **Prediction based**

Prediction-based – Training

Collect data:

潮水 退了 就 知道 誰 ...
不爽 不要 買 ...
公道價 八萬 一 ...
.....

**Minimizing
cross entropy**



Prediction-based - 推文接話

推 louisee :話說十幾年前我念公立國中時,老師也曾做過這種事,但

<https://www.ptt.cc/bbs/Teacher/M.1317226791.A.558.html>

推 AO56789:我同學才扯好不好，他有一次要交家政料理報告
→ AO56789:其中一個是要寫一樣水煮料理的食譜，他居然給我寫


著名簽名檔 (出處不詳)


Prediction-based – Language Modeling

$P(\text{"wreck a nice beach"})$

$= P(\text{wreck} | \text{START})P(\text{a} | \text{wreck})P(\text{nice} | \text{a})P(\text{beach} | \text{nice})$


$P(b | a)$: the probability of NN predicting the next word.






Bengio, Y., Ducharme, R., Vincent, P., & Jauvin, C. (2003). A neural probabilistic language model. *Journal of machine learning research*, 3(Feb), 1137-1155.

Prediction-based




- Take out the input of the neurons in the first layer
- Use it to represent a word w
- Word vector, word embedding feature: $V(w)$



Prediction-based

You shall know a word by the company it keeps



蔡英文
or
馬英九

The probability
for each word as
the next word w_i

“宣誓就職”
should have large
probability

Training text:

..... 蔡英文 宣誓就職


w_{i-1}

w_i

..... 馬英九 宣誓就職



w_{i-1}

w_i



Prediction-based

– Sharing Parameters



The length of \mathbf{x}_{i-1} and \mathbf{x}_{i-2} are both $|V|$.


The length of \mathbf{z} is $|Z|$.

$$\mathbf{z} = \mathbf{W}_1 \mathbf{x}_{i-2} + \mathbf{W}_2 \mathbf{x}_{i-1}$$

The weight matrix \mathbf{W}_1 and \mathbf{W}_2 are both $|Z| \times |V|$ matrices.

$$\mathbf{W}_1 = \mathbf{W}_2 = \mathbf{W} \Rightarrow \mathbf{z} = \mathbf{W} (\mathbf{x}_{i-2} + \mathbf{x}_{i-1})$$


Prediction-based – Sharing Parameters



Prediction-based


– Various Architectures

- Continuous bag of word (CBOW) model





predicting the word given its context

- Skip-gram




predicting the context given a word

Word Embedding



Source: <http://www.slideshare.net/hustwj/cikm-keynotenov2014>

Word Embedding



Fu, Ruiji, et al. "Learning semantic hierarchies via word embeddings." *Proceedings of the 52th Annual Meeting of the Association for Computational Linguistics: Long Papers*. Vol. 1. 2014.

Word Embedding

- Characteristics $V(\text{Germany}) \approx V(\text{Berlin}) - V(\text{Rome}) + V(\text{Italy})$

$$V(\text{hotter}) - V(\text{hot}) \approx V(\text{bigger}) - V(\text{big})$$

$$V(\text{Rome}) - V(\text{Italy}) \approx V(\text{Berlin}) - V(\text{Germany})$$

$$V(\text{king}) - V(\text{queen}) \approx V(\text{uncle}) - V(\text{aunt})$$

- Solving analogies


Rome : Italy = Berlin : ?

Compute $V(\text{Berlin}) - V(\text{Rome}) + V(\text{Italy})$

Find the word w with the closest $V(w)$

Demo


- Machine learns the meaning of words from reading a lot of documents without supervision



Demo

- Model used in demo is provided by 陳仰德
 - Part of the project done by 陳仰德、林資偉
 - TA: 劉元銘
 - Training data is from PTT (collected by 葉青峰)


Multi-lingual Embedding





Bilingual Word Embeddings for Phrase-Based Machine Translation, Will Zou, Richard Socher, Daniel Cer and Christopher Manning, EMNLP, 2013

Document Embedding

- word sequences with different lengths → the vector with the same length
 - The vector representing the meaning of the word sequence
 - A word sequence can be a document or a paragraph




Semantic Embedding



Reference: Hinton, Geoffrey E., and Ruslan R. Salakhutdinov. "Reducing the dimensionality of data with neural networks." *Science* 313.5786 (2006): 504-507

Beyond Bag of Word

- To understand the meaning of a word sequence, the order of the words can not be ignored.



Beyond Bag of Word

- **Paragraph Vector**: Le, Quoc, and Tomas Mikolov. "Distributed Representations of Sentences and Documents." ICML, 2014
- **Seq2seq Auto-encoder**: Li, Jiwei, Minh-Thang Luong, and Dan Jurafsky. "A hierarchical neural autoencoder for paragraphs and documents." arXiv preprint, 2015
- **Skip Thought**: Ryan Kiros, Yukun Zhu, Ruslan Salakhutdinov, Richard S. Zemel, Antonio Torralba, Raquel Urtasun, Sanja Fidler, "Skip-Thought Vectors" arXiv preprint, 2015.

Acknowledgement

- 感謝 John Chou 發現投影片上的錯字