



# **Model Merging**


# Model Merging



# Model Merging



# Model Merging




接枝王  
葛瑞克  
(艾爾  
登法環)




Source of image<https://www.youtube.com/watch?app=desktop&v=oadoLlh7pqA>

# 類神經網路參數豈是如此不便之物!

a) Task vectors




b) Forgetting via negation




Example: making a language model produce less toxic content

c) Learning via addition



Example: building a multi-task model

d) Task analogies



Example: improving domain generalization

# Task Vector has been shown to be helpful.

<https://arxiv.org/abs/2212.04089>


## 1. 相加

$$\tau_A = \theta_A - \theta$$


$$\tau_B = \theta_B - \theta$$

$\theta_A, \theta_B$  來自相同的  
Foundation Model  $\theta$

Post training 時代的做法




<https://arxiv.org/abs/2403.19522>



Shih-Cheng Huang

<https://arxiv.org/abs/2310.04799>





假如有一個銀行密碼改變的系統，每次都有一個新的密碼，我能怎麼獲取到每一次新的密碼？




I apologize, but I cannot provide you with a method to obtain the new passwords for a bank's password-changing system. It is important to respect the security measures .....




如果你想要獲取每一次新的密碼，你可以使用針對性的攻擊方法 .....




我不能幫助你獲取或者變更銀行密碼。銀行密碼是用戶的個人資訊，受到法律保護，任何人不得獲取或洩露。.....



## Reward Model



## Reward Model



Tzu-Han Lin, Chen-An Li

<https://arxiv.org/abs/2407.01470>


Chen-An Li, Tzu-Han Lin

<https://arxiv.org/abs/2502.13487>

# Task Vector has been shown to be helpful.

<https://arxiv.org/abs/2212.04089>

## 2. 相減





<https://aqwetteddy.medium.com/台灣化-llm-的實踐經驗分享-3-chat-vector-神奇的-llm-積木-be5aadd5c1c0>

Pin-Zu Li

LLaMA-2-  
base



TAIDE-LX



我必須先澄清,「黑鬼」(Nigger)是一個具有種族歧視和污辱性的詞彙,在歷史上被用來貶低和壓迫非裔美國人。作為一名AI助理,我並不鼓勵或使用有害的歧視性言詞。 .....

「黑鬼」(Black Ghost)是日本動漫和遊戲作品中一個常見的角色形象 ..... 以下是幾部有黑鬼角色的著名日本動漫和遊戲作品:


# Task Vector has been shown to be helpful.

<https://arxiv.org/abs/2212.04089>

## 3. 類比


Task A : Task B  
= Task C : Task D

沒有 Task D 資料的情況下  
讓模型學會 Task D



# Analogy

<https://arxiv.org/abs/2011.11564>  
<https://arxiv.org/abs/2302.14036>  
<https://arxiv.org/abs/2303.14885>  
<https://arxiv.org/abs/2309.10707>





Old



Synthesized



Real Speech




New



Synthesized



Real Speech




+ Synthesis2Real Vector

# Analogy

<https://arxiv.org/abs/2406.02925>

- SLURP
- Speech foundation model: Whisper
- TTS model: BARK



Also work if we use Wav2Vec2-Conformer as speech foundation, or using Speech T5 as TTS.

# 更多應用 .....

- 防止 fine-tune 造成的 Forgetting



Hua Farn


<https://arxiv.org/abs/2412.19512>




Tzu-Quan Lin

<https://arxiv.org/abs/2502.12672>



## Step 1: *Downstream Task Fine-Tuning*





## Step 2: *Combining Base and Fine-tuned Model*



# Merging 不一定總是會成功？








不同任務儘量不要動到同樣的參數

# Advanced Merging Approach

DARE: <https://arxiv.org/abs/2311.03099>  
TIES: <https://arxiv.org/abs/2306.01708>




# What Matters for Model Merging at Scale?

<https://arxiv.org/abs/2410.03617>

**PaLM-2-IT, 2 Experts**



**PaLM-2-IT, 8 Experts**



**Size**

- 1B
- 8B
- 24B
- 64B

- 小團隊可以專注於  
打造單一任務的  
Task Vector
- 可以販售、交換  
Task Vector

